Date: 27.09.2022

SHORT NOTICE INVITING TENDER (SNIT)

Sealed tender for the following urgent work under AIDC Ltd. is hereby invited from intending reputed Company / Firms / registered contractors of PWD (Road) / PWD (Building) with financially sound background as detailed below:-

S1	Details of works	Estimated	Tender Fee and Earnest	Completion
No.		cost	money to be deposited in	time
		inclusive of	form of Demand draft in	
		all Taxes	favour of "Assam	
	v z		Industrial Development	
			Corporation Ltd [*] and	
	2		payable at Guwahati.	0
1	Repairing of electrical	Rs.46,664/-	Tender Fee: Rs.500/-	7 days
	works at Admin Building,		(Rupees five hundred	
	EPIP, Amingaon,		only) which is non-	
	Kamrup, Assam		refundable.	
			EMD: Rs.1,000/- for	
			General Category and	
			Rs.500/- for SC/ST/ OBC	
			category	

The BOQ with specifications for the work can be downloaded from **AIDC's website** www.aidcltd.com

The sealed tender for the work will be received up to **2.00 PM (IST)** on **07.10.2022** in the office of the AIDC Ltd., R.G Baruah Road, Guwahati-781024 and will be opened on the same day in presence of interested bidders or their authorised representatives at **3.00 PM (IST)**. In the event of the office remaining closed under unavoidable circumstances, the tender will be received on next working day up to the stipulated time. The envelope containing the tender paper should be distinctly marked.

Terms & Conditions:

- 1) Completion period for the work is 7 (seven) days from the issue of the work orders or handing over the site whichever is earlier.
- 2) The contract price is inclusive of all Taxes in connection with execution of the contract.
- 3) The bidder should have the experience of successful execution of similar works under any Govt. Agency and to produce the same along with the bid documents.
- 4) One copy of PAN Card, GSTIN No. with Bank details should be submitted.
- 5) Other terms & conditions will be mentioned in due course of time in the Work Order.

and the same of th

The quoted rate should be computer typing and both in figure and words. The offered bid should not be in percentage basis. Bid should be submitted for each item with required tender fee, earnest money and documents. The bids without requisite tender fee and EMD will be rejected.

The Managing Director, AIDC reserve the right to accept or reject any or the entire proposal without assigning any reason thereof.

(A. Saikia)

Deputy General Manager (Tech)

BOQ FOR THE WORK OF "REPAIRING OF ELECTRICAL WORKS AT ADMIN BUILDING, EPIP, AMINGAON, KAMRUP, ASSAM"

Description	Unit	Quantity	Rate (in Rs.)	Amount (in Rs.)
Providing & laying of LT XLPE Cable 3.5 Core 25 sq mm (Aluminium) armoured.	RM	120		
Supply including fitting and fixing of Resin Cast type 1.1 KV PVC/XLPE/PILC cable Straight through Jointing Kits (MS - SE AL make) including all accessories for the following sizes including testing and commissioning as specified and directed by the Deptt. 25.00 & 35.00 Sq.mm., 3.5 Core cable.	Each	3		
Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation: B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min , 350 RPM (tolerance as per IS: 374-2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise=75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc.	Each			
Repairing of existing ceiling fan including providing & installation of required cable & switch, etc. and all the other required material.	Each	5		
Wiring for fan point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	Point	1		
	Providing & laying of LT XLPE Cable 3.5 Core 25 sq mm (Aluminium) armoured. Supply including fitting and fixing of Resin Cast type 1.1 KV PVC/XLPE/PILC cable Straight through Jointing Kits (MS - SE AL make) including all accessories for the following sizes including testing and commissioning as specified and directed by the Deptt. 25.00 & 35.00 Sq.mm., 3.5 Core cable. Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation: B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min , 350 RPM (tolerance as per IS: 374-2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise=75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc. complete as required. Repairing of existing ceiling fan including providing & installation of required cable & switch, etc. and all the other required material. Wiring for fan point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single	Providing & laying of LT XLPE Cable 3.5 Core 25 sq mm (Aluminium) armoured. Supply including fitting and fixing of Resin Cast type 1.1 KV PVC/XLPE/PILC cable Straight through Jointing Kits (MS - SE AL make) including all accessories for the following sizes including testing and commissioning as specified and directed by the Deptt. 25.00 & 35.00 Sq.mm., 3.5 Core cable. Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation: B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min, 350 RPM (tolerance as per IS: 374-2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise=75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc. complete as required. Repairing of existing ceiling fan including providing & installation of required cable & switch, etc. and all the other required material. Wiring for fan point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	Providing & laying of LT XLPE Cable 3.5 Core 25 sq mm (Aluminium) armoured. Supply including fitting and fixing of Resin Cast type 1.1 KV PVC/XLPE/PILC cable Straight through Jointing Kits (MS-SE AL make) including all accessories for the following sizes including testing and commissioning as specified and directed by the Deptt. 25.00 & 35.00 Sq.mm., 3.5 Core cable. Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation: B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min , 350 RPM (tolerance as per IS : 374-2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise=75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc. complete as required. Repairing of existing ceiling fan including providing & installation of required cable & switch, etc. and all the other required material. Wiring for fan point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	Providing & laying of LT XLPE Cable 3.5 Core 25 sq mm (Aluminium) armoured. Supply including fitting and fixing of Resin Cast type 1.1 KV PVC/KLPE/PILC cable Straight through Jointing Kits (MS - SE AL make) including all accessories for the following sizes including testing and commissioning as specified and directed by the Deptt. 25.00 & 35.00 Sq.mm., 3.5 Core cable. Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation: B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min , 350 RPM (tolerance as per IS : 374-2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise=75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc. complete as required. Repairing of existing ceiling fan including providing & installation of required cable & switch, etc. and all the other required material. Wiring for fan point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.

Rupees in words:

A S